



MAGNUM NEW PLUS READY MIX JOINT COMPOUND

Magnum New Plus compound is a ready-to-apply super fine finishing compound formulated for smooth finishing coats, for skim-coating entire interior wallboard surfaces, plaster walls and ceilings, and covering all kinds of wood surfaces.

It is ideal for delicate white finished stencil work that does not need to be painted. When used as a finishing coat, it makes the surface entirely smooth and ready for paint.

Magnum New Plus offers the following advantages:

- ✓ Super Fine Smooth Texture
- ✓ Prepares Surface For Paint or Other Decoration
- ✓ Factory Pre-Mixed



www.gpclarkinternational.com

Superior Finishing Products



MAGNUM NEW PLUS READY MIX COMPOUND

PRODUCT TECHNICAL DATA

REFERENCE

Magnum New Plus Ready Mix Compound

USAGE

A super fine ready-to-apply vinyl formulation for smooth finishing coats, for skim-coating entire interior wallboard surfaces, plaster walls and ceilings, and covering all kinds of wood surfaces, applying simple textures and all other fine finishing. It is ideal for delicate white stencil work that does not need to be painted. When used as a finishing coat, it makes the surface entirely smooth and ready for paint.

COVERAGE

0.30 – 0.18 KG/M2 Applied.

COLOR

White

PACK SIZE

25 KG in plastic pail.

SOLID CONTENT

Approximately 67 %

APPLICATION

Apply directly from pail by hand using a trowel, drywall knife or any other instrument.

FLASH POINT

None.

TEMPERATURE RANGE

Recommended application temperature 10 °C - 47 °C.

STORAGE

Protect from freezing, direct sunlight, and extreme heat over 65 °C. Rotate stock every 90 days.

COMPOSITION

- Fine-graded white calcium carbonate
- vinyl-based
- additives to improve handling properties
- preservative, and rust inhibitor

DRYING TIME

4 hours per millimeter of thickness when applied with a temperature of + 16 °C with a relative humidity of around 70 - 80 %.

CLEAN

Fresh water.

STANDARDS

Meets ASTM C 475 - 89

PRECAUTIONS

Must not be taken internally.
Keep Out Of Reach Of Children.



G.P.Clark International Distribution, L.L.C.
USA - 27906 E. Colbern Road
Lake Lotawana, MO 64086-8423
TEL. +1-877-900 8510
FAX +1-816-774 3777

G.P. Clark, S.A.L.
LEBANON - Halat Factory
P.O.Box 384 Zouk Michael
TEL. +961-9-478 540/1/3/4
FAX +961-9-478 542

G.P. Clark GCC Building Materials Trading L.L.C
UAE-Dubai- Deyaar Barsha Building
First Floor- Office#117
P.O.Box 391998 - Dubai
TEL / FAX +971 -4 - 399 7399